PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

| Applicant's or agent's file reference P804032/WO/1 | FOR FURTHER ACT | TION | See Form PCT/IPEA/416 |
|---|--|---------------------------------------|---|
| International application No. PCT/DE 03/03645 | International filing date 11/03/2003 | (day/month/year) | Priority date (day/month/year) 11/07/2002 |
| International Patent Classification (IPC) | or national classification a | nd IPC | <u> </u> |
| C23C18/16 | | | |
| Applicant MTU AERO ENGINES GMBH et | al. | | , |
| This report is the international part Authority under Article 35 and tr | | | y this International Preliminary Examining 36. |
| 2. This REPORT consists of a total | ofsheets, in | ncluding this cover s | heet. |
| 3. This report is also accompanied b | | | |
| a. 🚺 (sent to the applicant a | and to the International Bu | <i>reau)</i> a total of 9 | sheets, as follows: |
| | ontaining rectifications au | | been amended and are the basis of this report hority (see Rule 70.16 and Section 607 of the |
| | closure in the internationa | | ty considers contain an amendment that goes I, as indicated in item 4 of Box No. I and the |
| | , containing | a sequence listing | ype and number of electronic carrier(s)) and/or tables related thereto, in computer to Sequence Listing (see Section 802 of the |
| Administrative Instruct | | | |
| 4. This report contains indications r | elating to the following ite | ems: | |
| Box No. I Basis of the | e report | | |
| Box No. II Priority | | | |
| | • | egard to novelty, inv | entive step and industrial applicability |
| | ity of invention | | |
| | tatement under Article 35(nd explanations supporting | | elty, inventive step or industrial applicability; |
| Box No. VI Certain doc | cuments cited | | · |
| Box No. VII Certain def | ects in the international ap | plication | |
| Box No. VIII Certain obs | servations on the internation | onal application | |
| Date of submission of the demand | | Date of completio | n of this report |
| 05/14/2004 | | 01/17/2005 | |
| Name and mailing address of the IPEA/ | · · · · · · · · · · · · · · · · · · · | Authorized officer Hintermaier, F. | |
| Facsimile No | | Telephone No | |

International application No.

PCT/DE 03/03645

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

| Box N | o. I | Basis of the report | | |
|---------|---|---|--|--|
| | | ard to the language, this report is based on the international application in the language in which it was filed, unless e indicated under this item. | | |
| | Th wh | his report is based on translations from the original language into the following language, hich is the language of a translation furnished for the purposes of: | | |
| | | international search (under Rules 12.3 and 23.1(b)) | | |
| | | publication of the international application (under Rule 12.4) | | |
| | | international preliminary examination (under Rules 55.2 and/or 55.3) | | |
| fu | rnished | ard to the elements of the international application, this report is based on (replacement sheets which have been to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" not annexed to this report): | | |
| | the | e international application as originally filed/furnished | | |
| ✓ | | e description: | | |
| | | ges 1-11 as originally filed/furnished | | |
| | | received by this Authority on | | |
| | pag | ges* received by this Authority on | | |
| V | the | e claims: | | |
| | | ges 2-8 as originally filed/furnished | | |
| • | | ges* as amended (together with any statement) under Article 19 | | |
| | | ges* 1 received by this Authority on 09/17/2004 w/ letter 09/17/04 | | |
| | pag | ges* received by this Authority on | | |
| | the | e drawings: | | |
| | | ges as originally filed/furnished | | |
| | | ges* received by this Authority on | | |
| | pag | ges* received by this Authority on | | |
| | as | sequence listing and/or any related table(s) - see Supplemental Box Relating to Sequence Listing. | | |
| 3. |] | e amendments have resulted in the cancellation of: | | |
| J. L | , <u>, , , , , , , , , , , , , , , , , , </u> | - | | |
| | the description, pages | | | |
| | <u> </u> | the drawings cheete/Figs | | |
| | the drawings, sheets/figs the sequence listing (specify): | | | |
| | <u> </u> | any table(s) related to sequence listing (specify): | | |
| | | any table(s) lefated to sequence fisting (specify). | | |
| 4. | ma | is report has been established as if (some of) the amendments annexed to this report and listed below had not been ade, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box ule 70.2(c)). | | |
| | Г | the description, pages | | |
| | | the claims, Nos. | | |
| | | the drawings, sheets/figs | | |
| | | the sequence listing (specify): | | |
| | | any table(s) related to sequence listing (specify): | | |
| | | | | |
| * If it | tem 4 ap | pplies, some or all of those sheets may be marked "superseded." | | |

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/DE 03/03645

| Statement | | | |
|------------------------------------|------------------|-----|-------|
| Novelty (N) | Claims | 1-7 | YES |
| | Claims | 8 | NO NO |
| Inventive step (IS) | Claims Claims | 1.7 | YES |
| | Ciaims | 1-7 | NO NO |
| Industrial applicability (IA) | Claims Claims | 1-8 | |
| | | | |
| Citations and explanations (Rule 7 | 0.7) | | |
| ee appended sheet | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | · | |
| | | · | |
| | | | |
| | | | |
| | | | |

PCT/DE2003/03645 Appended Sheet

Re Point V.

Substantiated Determination under Rule 66.2(a)(ii), Regarding Novelty, Inventive Activity, and Industrial Applicability; Documents and Explanations in Support of this Determination

- The following documents cited in the search report are named in this report of examination:
 - D1: DE 40 24,911 A (ASEA BROWN BOVERI) April 11, 1991 (1991-04-11)
 - D2: US-A-4,895,625 (THOMA[sic] MARTIN ET AL) Jan. 23, 1990 (1990-01-23)
 - D3: DE 37 16 935 A (MOTOREN TURBINEN UNION) December 1, 1988 (1988-12-01)
 - D4: SU-A-1 803 480 (DNEPROVSKIJ NII T MASH; N PROIZV OB EDINENIE MASH (SU) March 23, 1993 (1993-03-23)
 - D5: EP-A-0 748,394 (SERMATECH INT INC) December 18, 1996 (1996-12-18)
 - D6: WO 94/1,9583 A (BAJ COATINGS LTD; FOSTER JOHN (GB);
 TAYLOR ALAN (GB); CHATTERLEY M) September 1, 1994
 (1994-09-01)
 - D7: US-A-5,935,407 (NENOV KRASSIMIR P ET AL) August 10, 1999 (1999-08-10)
 - D8 WO 00/36180 A (JOSSO PIERRE; BACOS MARIE PIERRE (FR); ONERA (OFF NAT AEROSPATIALE) June 22, 2000 (2000-06-22)
- 2. Background Information.

PCT/DE2003/03645
Appended Sheet

- 2.1. D1 relates to the galvanic deposit of protective layers to apparatus parts that are exposed to oxidation and corrosion at high temperatures, such as in turbines (column 1, lines 6 - 11). In exemplary embodiment 1, which is greatly analogous to the exemplary embodiment of page 10 of the present Application, a gas turbine blade made of a nickel superalloy is first degreased and then pickled anodically in diluted HCl. Then a 1 µm Ni adhesion promoting layer is applied galvanically. Subsequently, 150 g of a Ni/Al powder, having a grain size of 10 - 50 μ m, are suspended in a 2.5 l nickel sulfamate bath. Depositing takes place at a current density of 500A/m². The bath is vibrated for this. The additionally added glass balls support the suspension and also make denser the galvanically deposited layer. A layer having a thickness of 1 mm is produced, which is subsequently exposed to homogenization at 1100°C for 3 hours.
- 2.2. D2 describes the production of protective coatings on component parts that are in contact with corrosive hot gas, such as gas turbine parts (column 1, lines 7 9). According to Claim 1, an electrolyte based on Co and or nickel is made available for this, in which a passivated powder of a metal alloy of Al and/or Cr is suspended. In this instance, the powder does not necessarily have to contain Cr. By passivating is meant providing the particles with an artificial oxide layer. After the galvanic deposit, the substrate is tempered. The powder has a particle size of 1 15 μ m.

PCT/DE2003/03645
Appended Sheet

- 2.3. D3 describes the preparation of a hot gas corrosion protective layer, e.g. on turbine blades. For this, in a NiSO₄ or in a CoSO₄ electrolytic bath, TiSi₂ particles having a diameter of 0.5 50 μm are suspended and a 10 1000 μm thick layer is deposited galvanically. In closing, tempering is carried out at 800°C (column 2, lines 21 56).
- 2.4. D4 also states a process for improving the corrosion resistance of component parts that are exposed to hot gas. For this purpose, a mixture of Al and W particles is suspended in a Ni electrolyte, and a protective layer is deposited which is tempered at 1200°C. Before being applied, the aluminum particles are treated with H₂SO₄, then washed and tempered in air at 190 230°C. In this context, an artificial oxide layer is generated on the Al particles.
- 2.5. D5, which is cited in the present Application, describes the improvement of the corrosion properties and the oxidation properties of turbine parts by applying a protective layer made of Al particles and Si particles, and is subsequently diffused in by heat treatment [0001, 0002, 0039 0049]. In [0012] and [0013] a protective layer from the related art is cited which is also made of Al particles and Si particles.
- 2.6. Finally, it is noted that it is part of the related art to improve the corrosion properties of parts exposed to hot gases, using protective coatings, which were obtained by galvanic depositing of particles based on Cr-Al-Y and

PCT/DE2003/03645 Appended Sheet

subsequent tempering (D6, D7). Currentless methods for depositing such layers are also known (D8).

- 3. Novelty (Article 33(2)PCT)
- 3.1. Claim 1 appears to be novel, since none of documents D1

 D8 describes an external currentless or electrolytic
 depositing of Pt to which additional particles have been added.
- 3.2. Claim 8 does not appear to be novel, since it is not clear why a protective layer produced by the method according to Claim 1 would be different from a layer produced according to the method as in D5. In D5 a layer is deposited successively that includes metals, which are also mentioned in Claim 1 of the present Application. This layer is tempered, same as that of Claim 1, the final protective layer being created thereby.
- 4. Inventive Step (Article 33(3) PCT).
- 4.1. D1 D4 state methods that include all the technical elements of Claim 1 except that in D1 D4 Ni and/or Co is deposited instead of Pt in an external currentless or electrolytic manner. D6 D8 also state methods in which particles are applied to a substrate together with a metal, by external currentless or electrolytic deposition of this metal. In all the cases D1 D4 and D6 D8 articles are coated, in this context, that are exposed to hot gas corrosion. By subsequent tempering of

PCT/DE2003/03645

Appended Sheet

the deposited layer, an alloy formation is achieved in this context, and the protective layer is formed.

- 4.2. It is sufficiently well known that the protective layers of such articles may also contain Pt. Thus, for example, D5 states that one should first deposit Pt electrolytically on the surface of a respective component, then apply a slurry of aluminum and silicon powder, and subsequently sinter at 660°C [0046, 0040]. D8 also mentions using noble metals in such coatings, Pt and Pd being preferred (Claims 1 and 4).
- 4.3. Consequently, it appears obvious also to use Ptcontaining electrolytes in conjunction with the methods
 named in D1 D4 and D6 D8 in producing hot gas
 corrosion protective layers, in order to arrive at a
 matrix of Pt-containing metal and particles which form
 said protective layer after a tempering step. In
 addition, D5 already makes it obvious that one should
 consider depositing Pt electrolytically for building up
 such corrosion protective layers. And finally, the
 present Application states no surprising effects that
 would be attributable to the use of Pt instead of Ni or
 Co in the electrolyte.
- 4.4. The further technical elements of dependent Claims 2 8 are already mentioned in documents D1 D8, or may be found by customary experimental activity. Thus, D1 already mentions the use of particles alloyed with Ni, having a grain size of 10 50 μm. In D2 a passivated powder is used which actually includes particles having

PCT/DE2003/03645
Appended Sheet

an artificial oxide layer. In D3, TiSi₂ particles are used as the powder. The use of Si particles for improving the corrosion properties is known from D5. The ascertainment of the optimal thickness of the protective layer is regarded as a routine method.

- 4.5. Finally, it is noted that it is part of the related art to improve the corrosion properties of parts exposed to hot gases, using protective coatings, which were obtained by galvanic depositing of particles based on Cr-Al-Y and subsequent tempering (D6, D7). Currentless methods for depositing such layers are also known (D8). The exclusion of Cr as component of the particles in Claim 1 consequently appears to be only the desire to produce novelty as compared to methods known per se. In any case, special non-obvious technical effects are not described for the exclusion of Cr in the present Application. On the contrary: according to page 3, lines 15 16, Cr may even be present.
- 5. Industrial Applicability.

Claims 1 - 8 satisfy the requirement of industrial applicability (Article 33(4) PCT), since the technical subject matter of the present Application may be industrially manufactured or used in a technical sense.

PCT/DE2003/03645
Appended Sheet

Re Point VII

Certain Defects in the International Application

The present Application does not correspond to the requirements of Rule 5.1(a)(ii)PCT, since the most proximate related art, e.g. documents D1 - D3 are neither mentioned in the introduction to the present invention nor is their content cited briefly.

Re Section VIII

Specific Remarks regarding the International Application 1.

- 1. Clarity
- 1.1. Claim 1 contradicts the specification on page 3, lines 15- 16, according to which the particles do not contain any Cr preferably, but not necessarily.
- 1.2. The definition of the oxide layer in Claim 2 is formulated in a vague manner: what are "normal environmental conditions"? This objection could be removed by making the thickness of the oxide layer more precise according to what is said on page 7, lines 23 25.
- 1.3. Having Claim 5 dependent on Claim 4 makes little sense: Si particles that are alloyed with Si.
- 2. The present Application does not satisfy the requirements of Article 5, PCT, since it does not put one skilled in the art into the position of executing the subject matter of Claim 1. Thus, the Application states no exemplary

PCT/DE2003/03645
Appended Sheet

embodiment from which it would be clear how the depositing using a Pt electrolyte would proceed, and which electrolyte would be appropriate for this.

New Claim

What Is Claimed Is:

- A method for coating a substrate, having the following steps
 - a) external current-less or electrolytic deposition of Pt or Pt and Co in a deposition bath known as such, in which additionally particles are suspended which contain at least one metal selected from Mg, Al, Ti, Zn and no Cr, the particles becoming occluded in the coating
 - b) heat treatment of the coated substrate.

1